

CFT02

Two-unit cabinet fan for 6/9/12U cabinet



- Integrated design, easy to install.
- Supports temperature adjustment; long service life.
- Included European power cord; compatible with power cords in other standards.

System Overview

The two-unit cabinet fan is applicable to a 6/9/12U cabinet and easy to install.

Technical Specification

Structure

| | |
|----------------------|--|
| Casing | Cold rolled sheet [width: 0.8 mm (0.03")] |
| Color | Black |
| Product Dimensions | 346 mm × 155 mm × 76 mm (13.62" × 6.10" × 2.99") |
| Net Weight | 1.1 kg (2.43 lb) |
| Gross Weight | 1.4 kg (3.09 lb) |
| Packaging Method | Paper box (10 pcs in one box) |
| Packaging Dimensions | Inner carton: 360 mm × 165 mm × 80 mm (14.17" × 6.50" × 3.15") Package: 380 mm × 355 mm × 316 mm (14.96" × 13.98" × 12.44") |
| Accessory | 1 × 1.2 m European standard power cord 8 × screws (M4.6 × 10) |

Electrical Performance

| | |
|------------------|---------------------------------|
| Voltage | 220 V |
| Frequency | 50–60 Hz |
| Rotational Speed | 2,200±10% RPM |
| Noise | 45 dB(A) |
| Airflow Volume | 68 CFM |
| Air Pressure | 6.4 mmH ₂ O |
| Power | 30 W |
| Lifespan | 30,000 hours at +25 °C (+77 °F) |

Environmental Performance

| | |
|-----------------------|--------------------------------------|
| Operating Temperature | −10 °C to +60 °C (+14 °F to +140 °F) |
| Operating Humidity | 20%–80% (RH), non-condensing |
| Storage Temperature | −10 °C to +60 °C (+14 °F to +140 °F) |
| Storage Humidity | 20%–80% (RH), non-condensing |

Certification

| | |
|----------------|----|
| Certifications | CE |
|----------------|----|

Ordering Information

| Type | Part Number | Description |
|------|-------------|--|
| Fan | CFT02 | Two-unit cabinet fan for a 6/9/12U cabinet |

Dimensions (mm[inch])

