# LifeSmart 窗帘电机智控器简易说明书

Typical Graphic Layout | Scale: 1/1

| 尺寸 | 60*60mm |
|----|---------|
| 纸张 | 80g书纸   |
| 工艺 |         |
|    |         |



MINS Curtain Motor Controller

Simply Brilliant

User Guide v1.0

#### PRODUCT INSTRUCTION

LifeSmart MINS Curtain Motor Controller can be combined with a traditional curtain motor to easy to install, and does not require wall wiring. It's powered by batteries and works independently without external power. It can be applied to curtain motor of various specifications.

communication and smart phone control. Users can control the curtain motor anytime and anywhere via mobile phone, set timing tasks, and

## PRODUCT INSTRUCTION


participate in smart scenes such as opening curtains when you're home, closing the curtains automatically when you leave home with other smart devices (Motion Sensors, Door/Window Sensors, etc.).

# SPECFICATIONS


| re                   | 135*32*23mm            |
|----------------------|------------------------|
| eight                | 55g (battery excluded) |
| terial               | PC+ABS                 |
| ttery                | AA LR6x2               |
| erating temperature  | -5~45°C                |
| erating humidity     | 5~90%                  |
| mmunication protocol | CoSS                   |
| reless frequency     | 433MHz                 |
| reless distance      | 100m (open field)      |

## **BUTTON & INTERFACE**

ATTENTION




## INTERFACE DEFINITION



#### INTERFACE DEFINITION

Input interface definition (connect physical switch)



#### INTERFACE

200±10mm

LifeSmart's MINS Curtain Motor Controller must be paired with Smart Station to work in the smart home system.

INSTALLATION INSTRUCTION

- ① Open the battery back panel of MINS curtain motor controller from the side and put
- ② After configuration of the Smart Station, click "+" on the home page of the App, then click "Add New Device", select "MINS Curtain Motor Controller" to enter the

#### INSTALLATION INSTRUCTION

- ③ Press and hold the pairing button for more than 5 seconds until the indicator light flashes. Enter the pairing state, click "Start Pairing";
- 4 Follow the instructions on App and complete the pairing operation;
- (5) If pairing is not successful, repeat steps 2-4 until the pairing is successful;

# 反面

#### INSTALLATION INSTRUCTION

(6) Install the battery back panel, connect MINS curtain motor controller to the curtain motor through the RJ11 output interface (please make sure that the cables are in right order). Operate the motor on the test whether it functions properly;



#### INSTALLATION INSTRUCTION



(8) MINS curtain motor controller can set timer tasks, trigger smart scenes and so on. Please explore more on LifeSmart App.

#### IN YOUR PACKAGE

RJ11 Cable

User Guide

www.ilifesmart.com

 MINS Curtain Motor Controller (7) (Optional) If there is a physical switch, connect AA LR6 Battery the RJ11 input interface to the physical switch;



WARRANTY DESCRIPTION

support@ilifesmart.com / LifeSmart CERTIFICATION

#### WARRANTY DESCRIPTION

problems that arise under normal usage, LifeSmart

will provide a free replacement.

Thank you for purchasing this LifeSmart product. In order to protect your rights, please read the following content carefully: The warranty period of our company's products is one year from the date with the product instructions; of purchase or longer if local laws impose a longer minimum term, in which case the minimum term is Products beyond the warranty period; the warranty period. During the warranty period, any faults caused by the product itself or for quality or removed;

# use, and maintenance that is not in accordance

Products that have the barcode tampered with

Positive

electrode

Negative ...

 Devices that have been tampered with or customized outside of LifeSmart Terms Of Service as on the LifeSmart APP and website;

### ATTENTION

- The following conditions are not covered by the User-caused damage, such as inappropriate voltage input, high temperature, accidental spillage, physical damage, etc; Product failure or damage caused by installation,
  - Product failure or damage caused by force majeure such as earthquakes, fires, or floods;
  - Product failure or damage caused by other problems except the product itself.

#### DECLARATION

Technology Co., Ltd. As for the trademarks, product logos and product names from other companies presented within this manual, they are possessed by their own right holders. Without our written permission, no entity or individual shall extract, copy or disseminate in part or the whole of the manual contents in any form. Due to product version upgrades or other reasons, content of this manual may change. Our company reserves the right to change the contents of this manual without any notice.

#### DECLARATION

LifeSmart is a trademark of Hangzhou LifeSmart This manual is used only for instructional purposes. We strive to provide accurate information in this manual, but we are not able to ensure that the content of this manual is current. Statements, information and advice in this manual do not constitute any expressed or implied assurance. Updated manuals are available on our website at www.ilifesmart.com or by contacting

#### DECLARATION

Manufacturer: Hangzhou LifeSmart Technology Co., Ltd. 352 Binkang Road, Binjiang District, Hangzhou, Zhejiang,



Facebook: ilifesmarthome Twitter: ilifesmarthome Copyright © 2019 LifeSmart Inc. All Rights Reserved. P/N:8800XXX0 A0